## NSN 5305-01-070-8068

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-070-8068 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.470 inches **Fastener Length:** 1.250 inches **Head Style:** Hexagon **Head Height:** 0.160 inches Width Between Flats: 0.375 inches Point Length: 0.040 inches **First Diameter From Head:** 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.780 inches Point Style: Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 120.0 degrees Material: Steel comp 630 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5305-01-070-8068

Externally Relieved Body Screw - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A003b0