NSN 5305-01-070-9156

Close Tolerance Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-070-9156

| Thread Class: 3a Thread Direction: Right-hand Thread Length: 0.438 inches Fastener Length: |
|--|
| Thread Direction: Right-hand Thread Length: 0.438 inches |
| Right-hand Thread Length: 0.438 inches |
| Thread Length: 0.438 inches |
| 0.438 inches |
| |
| Fastener Length: |
| |
| Between 0.860 inches and 0.890 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.573 inches and 0.635 inches |
| Grip Diameter: |
| Between 0.3110 inches and 0.3120 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 0.428 inches and 0.448 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hardness Rating: |
| 46.0 rockwell c and 49.0 rockwell c |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel |
| Material Specification: |
| Ams 6487 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Nas 672 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

NSN 5305-01-070-9156

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

