

View Online at <https://aerobasegroup.com/nsn/5305-01-070-9610>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.945 inches and 1.000 inches

Fastener Length:

Between 0.970 inches and 1.000 inches

Head Style:

Fillister

Head Diameter:

Between 0.083 inches and 0.096 inches

Head Height:

Between 0.037 inches and 0.045 inches

Internal Drive Style:

Slot

Thread Diameter:

0.060 inches

Thready Qty Per Inch (tpi):

80

Min. Tensile Strength (psi):

55000 pounds per square inch

Screw Material:

Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 270 or copper alloy 274 or copper alloy 342 or copper alloy 353 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 377 or copper alloy 210 or copper alloy 220 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770

Screw Material Specification:

Qq-b-626 federal specification all material responses

Screw Surface Treatment:

Nickel

Screw Surface Treatment Specification:

Qq-n-290, cl 1 type 7 federal specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

1 type and 4s style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0