NSN 5305-01-071-1474

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-071-1474 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.608 inches and 0.688 inches **Fastener Length:** Between 0.658 inches and 0.688 inches **Head Style:** Hexagon **Head Height:** Between 0.049 inches and 0.060 inches Width Between Flats: Between 0.181 inches and 0.187 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4037 or steel comp 8630 **Screw Material Specification:** Mil-s-7839 military specification all material responses **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Thread Series Designator:**

Unjc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A500d0

NSN 5305-01-071-1474

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-7839 spec.