NSN 5305-01-071-4583

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-071-4583
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.250 inches
Fastener Length:
1.075 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.155 inches and 0.167 inches
Head Height:
Between 0.044 inches and 0.054 inches
First Diameter From Head:
Between 0.098 inches and 0.099 inches
Second Diameter From Head:
Between 0.061 inches and 0.063 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.415 inches and 0.425 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.825 inches
Internal Drive Style:
Slot
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
56
Externally Relieved Body Diameter Quantity:
2
Material:
Steel comp 303
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
C190000120 fscm 88818 mfr ref single treatment response
Thread Series Designator:
Unc
Shelf Life:

N/a

NSN 5305-01-071-4583

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0