## NSN 5305-01-071-6486

Socket Head Cap Screw - Page 1 of 2





Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.147 inches and 0.188 inches
Fastener Length:
Between 0.183 inches and 0.188 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.134 inches and 0.140 inches
Head Height:
Between 0.083 inches and 0.086 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.086 inches
Width Across Flats:
0.078 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
35.0 rockwell c and 42.0 rockwell c
Material:
Steel comp 410 or steel comp 416
Material Specification:
Qq-s-763 cond a federal specification 1st material response or astm a582 cond a assn standard 2nd material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Νο

## NSN 5305-01-071-6486

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

