NSN 5305-01-071-8132

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-071-8132

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.714 inches and 0.807 inches |
| Fastener Length: |
| Between 0.844 inches and 0.875 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.270 inches and 0.332 inches |
| Locking Feature: |
| Pellet threads |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2 cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1189 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-071-8132

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0