NSN 5305-01-071-8747

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-071-8747 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.074 inches and 0.089 inches **Fastener Length:** Between 0.172 inches and 0.177 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.170 inches and 0.180 inches **Head Height:** Between 0.045 inches and 0.055 inches **First Diameter From Head:** Between 0.072 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.088 inches and 0.098 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 410 or steel comp 416 **Material Specification:** Qq-s-763 cond a federal specification 1st material response or astm a582 cond a assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 2 or type 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-071-8747

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0