

View Online at <https://aerobasegroup.com/nsn/5305-01-071-8752>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.562 inches

**Fastener Length:**

0.562 inches

**Head Style:**

Watertight

**Head Diameter:**

0.347 inches

**Head Height:**

0.115 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Features Provided:**

O ring

**Thready Qty Per Inch (tpi):**

32

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

1980032, fscm 49671 mfr ref single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0