NSN 5305-01-072-2147

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-072-2147 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.215 inches **Fastener Length:** 0.410 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **First Diameter From Head:** Between 0.148 inches and 0.152 inches **Second Diameter From Head:** Between 0.105 inches and 0.107 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.079 inches and 0.099 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.100 inches and 0.116 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Special Features:** End with 45 degree chamfer to a point 0.070 in. Dia Material: Stainless steel **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment:** Oxide **Surface Treatment Specification:**

Mil-c-13924, cl 4 military specification single treatment response

Unf

Thread Series Designator:

NSN 5305-01-072-2147

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
NO
Fiig:

Mil-std (military Standard):

Mil-c-13924 spec.