

View Online at <https://aerobasegroup.com/nsn/5305-01-072-2147>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.215 inches

**Fastener Length:**

0.410 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**First Diameter From Head:**

Between 0.148 inches and 0.152 inches

**Second Diameter From Head:**

Between 0.105 inches and 0.107 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.079 inches and 0.099 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.100 inches and 0.116 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

2

**Special Features:**

End with 45 degree chamfer to a point 0.070 in. Dia

**Material:**

Stainless steel

**Material Specification:**

Qq-s-763 federal specification single material response

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924, cl 4 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.