## NSN 5305-01-072-5750

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-072-5750 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** Between 0.119 inches and 0.123 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.344 inches and 0.375 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment:** Passivate and oxide **Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response and mil-c-13924, class 4 or 2 military specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-072-5750

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.