NSN 5305-01-072-9126

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-072-9126



Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 0.871 inches and 0.952 inches Fastener Length: Between 0.969 inches and 1.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.191 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924 cl 2 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 3c style **Departure From Cited Document:** As modified by plating Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

NSN 5305-01-072-9126

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-c-13924 spec.

