NSN 5305-01-072-9143

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-072-9143 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.490 inches and 0.557 inches **Fastener Length:** Between 0.875 inches and 0.922 inches **Head Style:** Fillister countersunk **Head Diameter:** Between 0.390 inches and 0.395 inches **Head Height:** 0.015 inches **Shoulder Diameter:** 0.264 inches first shoulder and 0.265 inches first shoulder **Shoulder Length:** 0.365 inches first shoulder and 0.375 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life: N/a

NSN 5305-01-072-9143

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0