Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-072-9488

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.200 inches
Fastener Length:
Between 0.535 inches and 0.540 inches
Head Style:
Flat chamfer
Head Diameter:
0.440 inches
Head Height:
Between 0.190 inches and 0.198 inches
First Diameter From Head:
Between 0.135 inches and 0.145 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.075 inches and 0.085 inches
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Material:
Steel
Material Specification:
Ams 5738, 303se, cond b assn standard single material response
Surface Treatment:
Chromium
Surface Treatment Specification:
Mil-c-14538 military specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-072-9488

Externally Relieved Body Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-c-14538 spec.