NSN 5305-01-073-1487

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-073-1487 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.442 inches and 0.492 inches **Fastener Length:** Between 0.640 inches and 0.670 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.429 inches and 0.477 inches **Shoulder Diameter:** 0.327 inches first shoulder and 0.328 inches first shoulder **Shoulder Length:** 0.124 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder **Special Features:** Hex drive in thd end 0.127 in.Min 0.129 in. Maximum width across flats Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 92215-ht4010 manufacturers standard

Shelf Life:

N/a

NSN 5305-01-073-1487

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0