## NSN 5305-01-073-5738

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-073-5738 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.443 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.231 inches and 0.279 inches **Locking Feature:** Strip threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 8735 fastener or steel comp 6150 fastener **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1189 professional/industrial association standard

**Unit Of Measure:** 

N/a

Shelf Life:

## NSN 5305-01-073-5738

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0