## NSN 5305-01-073-6993

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-073-6993 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.240 inches and 0.250 inches **Fastener Length:** 0.938 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.370 inches and 0.390 inches **Head Height:** Between 0.422 inches and 0.452 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.532 inches and 0.542 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 or steel comp 304 **Material Specification:** Astm a582 assn standard single material response or qq-s-763 federal specification 2nd material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl 4 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-073-6993

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.