NSN 5305-01-073-6994

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-073-6994

| The state of the s |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 2.015 inches and 2.124 inches |
| Fastener Length: |
| Between 2.109 inches and 2.156 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.105 inches and 0.120 inches |
| Width Between Flats: |
| Between 0.302 inches and 0.313 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| Between 26.0 rockwell c and 32.0 rockwell c |
| Screw Material: |
| Steel comp 4037 or steel comp 8630 |
| Screw Material Specification: |
| Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response |
| Screw Surface Treatment: |
| Cadmium and chromate |
| Screw Surface Treatment Specification: |
| Qq-p-416 type 2 cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Specification Data: |
| 80205-nas1096 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

No

NSN 5305-01-073-6994

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.