## NSN 5305-01-073-9161

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-073-9161 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.532 inches and 0.625 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4340 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response Color: Black **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-073-9161

Machine Screw - Page 2 of 2



Fiig:

A500d0