## NSN 5305-01-074-0165

Machine Screw - Page 1 of 2

**Thread Class:** 

No

View Online at https://aerobasegroup.com/nsn/5305-01-074-0165



## 3a **Thread Direction: Right-hand Thread Length:** Between 1.483 inches and 1.656 inches Fastener Length: Between 1.609 inches and 1.656 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.305 inches and 0.314 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Screw Material: Steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1801 professional/industrial association standard Shelf Life: N/a Unit Of Measure: ---**Demilitarization:**

## NSN 5305-01-074-0165

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-5000 spec.

