NSN 5305-01-074-6018

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-074-6018

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.650 inches |
| Fastener Length: |
| 0.650 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| 0.320 inches |
| Head Height: |
| 0.100 inches |
| Shoulder Diameter: |
| 0.182 inches first shoulder and 0.187 inches first shoulder |
| Shoulder Length: |
| 0.400 inches first shoulder |
| Internal Drive Style: |
| W/o internal drive |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Shoulder Shape: |
| Round first shoulder |
| Special Features: |
| Head is slotted across dia., .050in. W, .050 in. Deep |
| Material: |
| Steel |
| Material Specification: |
| Bs970303s21 mfr ref single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 military specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5305-01-074-6018

Shoulder Screw - Page 2 of 2



| em | | | |
|----|--|--|--|
| | | | |

No

Fiig:

A003b0

Mil-std (military Standard):

spec.