NSN 5305-01-074-6832

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-074-6832 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.225 inches and 0.318 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.231 inches and 0.279 inches **Locking Feature:** Pellet threads or strip threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1189 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-074-6832

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0