Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-074-6833



Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.657 inches and 0.750 inches Fastener Length:
Thread Direction: Right-hand Thread Length: Between 0.657 inches and 0.750 inches
Right-hand <b>Thread Length:</b> Between 0.657 inches and 0.750 inches
Thread Length: Between 0.657 inches and 0.750 inches
Between 0.657 inches and 0.750 inches
Fastener Length:
-
Between 0.719 inches and 0.750 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Locking Feature:
Strip threads
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1190 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 5305-01-074-6833

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

