3a

24

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-074-6839



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.137 inches and 0.250 inches Fastener Length: Between 0.220 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.156 inches and 0.159 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 155000 pounds per square inch Surface Finish: 63.0 microinches bearing surface of head Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-074-6839

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

