NSN 5305-01-075-0974

Hexagon Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-075-0974

Right-hand Thread Length: 0.750 inches Fastener Length: 1.500 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541
Fastener Length: 1.500 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Fastener Length: 1.500 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
1.500 inches Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Head Style: Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Hexagon Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Head Height: Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Between 0.150 inches and 0.163 inches Width Between Flats: Between 0.428 inches and 0.438 inches Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Width Between Flats: Between 0.428 inches and 0.438 inches Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Between 0.428 inches and 0.438 inches Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Thread Diameter: 0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
0.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Features Provided: Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material:
Material:
Steel comp 1541
Thread Series Designator:
Unf
Specification Data:
81343-grade 6 professional/industrial association specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0