Hexagon Head Cap Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-075-1543

Thread Direction: Right-hand Thread Length: 1.000 inches Fastener Length: 1.250 inches Head Style: Head Style: Head Style: Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpl): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: Na Tot Measure: T Diminitrazion: Na Bilistriation: Na	
Thread Length: 1.000 inches Fastener Length: 1.250 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches With Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Quy Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Materia: 12000 pounds per square inch Materia: 12000 pounds per square inch Materia: <td< td=""><td>Thread Direction:</td></td<>	Thread Direction:
 1.000 inches Fastener Length: 1.250 inches Head Style: Head Style: Head Style: Head Height: Between 0.226 inches and 0.243 inches With Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Fastures Provided: Finished head Thready Qty Per Inch (tpi): 15 Min. Tensile Strength (psi): 15000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Materia! Steel comp 1541 Thread Series Designator: Unc Specification Data: Specification Data: Na Thid Measure: Na Fig: Na Fig: 	Right-hand
Fastener Length: 1.250 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches With Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Fatures Provided: Fatures Provided: Fatures Provided: Finshed head Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Inc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: Iva Iva Iva Formiltarization: Iva Formiltarization: Iva Steif Life: Iva	Thread Length:
1.250 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Imiliarization: No Fig:	1.000 inches
Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.251 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Imitiarization: No Fig:	Fastener Length:
Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Init of Measure: Pemilitarization: No Fig:	1.250 inches
Hea Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Sheff Life: N/a Unit Of Measure: Image:	Head Style:
Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Sheff Life: N/a Unic f Measure: N/a B0204-grade 6 professional/industrial association standard Sheff Life: N/a Unic f Measure: N/a Dini of Measure: N/a Dini of Measure: N/a Dini of Measure: No Fig:	Hexagon
Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Head Height:
Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit of Measure: Demilitarization: No Fig:	Between 0.226 inches and 0.243 inches
Thread Diameter:0.375 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):16Min. Tensile Strength (psi):154000 pounds per square inchMinimum Yield Strength:120000 pounds per square inchSpecial Features:Cold forged; protected by perma plate finish; double heat treated; 100 per pkgMaterial:Steel comp 1541Thread Series Designator:UncSpecification Data:80204-grade 6 professional/industrial association standardShelf Life:N/aInti Of Measure:Demilitarization:NoFig:	Width Between Flats:
0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Inti Of Measure: Demilitarization: No	Between 0.551 inches and 0.562 inches
Features Provided:Finished headFineady Qty Per Inch (tpi):16Min. Tensile Strength (psi):154000 pounds per square inchMinimum Yield Strength:120000 pounds per square inchSpecial Features:Cold forged; protected by perma plate finish; double heat treated; 100 per pkgMaterial:Steel comp 1541Thread Series Designator:UncSpecification Data:R0204-grade 6 professional/industrial association standardShelf Life:N/aDint Of Measure:Demilitarization:NoFig:	Thread Diameter:
Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.375 inches
Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Features Provided:
16 Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Mit Of Measure: Demilitarization: No	Finished head
Min. Tensile Strength (psi): 154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: So204-grade 6 professional/industrial association standard Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	Thready Qty Per Inch (tpi):
154000 pounds per square inch Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	16
Minimum Yield Strength: 120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Min. Tensile Strength (psi):
120000 pounds per square inch Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	154000 pounds per square inch
Special Features: Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No	Minimum Yield Strength:
Cold forged; protected by perma plate finish; double heat treated; 100 per pkg Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	120000 pounds per square inch
Material: Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Special Features:
Steel comp 1541 Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Ditt Of Measure: Demilitarization: No Fig:	Cold forged; protected by perma plate finish; double heat treated; 100 per pkg
Thread Series Designator: Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material:
Unc Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel comp 1541
Specification Data: 80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
80204-grade 6 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Unc
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	80204-grade 6 professional/industrial association standard
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
	No
A003b0	Fiig:
	A003b0