## NSN 5305-01-075-2060

Close Tolerance Screw - Page 1 of 2

3a

28

N/a





**Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.291 inches and 0.341 inches Fastener Length: Between 0.489 inches and 0.519 inches **Head Style:** Modified pan **Head Diameter:** Between 0.464 inches and 0.493 inches **Head Height:** Between 0.133 inches and 0.150 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches Grip Length: Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1144 professional/industrial association standard Shelf Life:

## NSN 5305-01-075-2060

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

