Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-075-6096



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.372 inches and 0.454 inches Fastener Length: Between 0.422 inches and 0.454 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches Hole Diameter: 0.036 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: 0.0937 inches **Hole Quantity:** 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 43.0 rockwell c Hole Configuration Style: Round internal hexagon **Product Name:** Navy special project Material: Steel comp 410 Surface Treatment: Passivate **Surface Treatment Specification:** Sps-b-178, fscm 56878 mfr ref single treatment response

NSN 5305-01-075-6096

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:

Unc

Specification Data:

56878-ks17 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0