## NSN 5305-01-075-7090

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-075-7090 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.635 inches and 0.794 inches **Fastener Length:** Between 1.205 inches and 1.225 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.490 inches and 0.528 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Three splines 120 degrees apart in body, thread to bedouble lead Material: Steel comp 8740 bearing surface of head or steel comp 4140 bearing surface of head **Material Specification:** Mil-s-8740 military specification 1st material response fastener or mil-s-5626 military specification 2nd material response fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416 type 2 cl2 federal specification single treatment response fastener **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Mil-std (military Standard):

Mil-s-8740 spec.

Fiig: A003b0