# NSN 5305-01-075-7092

Panel Fastener Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-075-7092



# **Thread Class:**

3a

Thread Length:

0.645 inches

# Fastener Length:

Between 0.925 inches and 0.945 inches

#### Head Style:

Flat countersunk

#### Head Diameter:

Between 0.518 inches and 0.528 inches

# Internal Drive Style:

Hexagon

# Thread Diameter:

0.375 inches

# Width Across Flats:

# 0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

# Countersink Angle:

Between 99.0 degrees and 101.0 degrees

# **Special Features:**

3 splines 0.040 in. Wide by 0.029 in. Deep 120 degrees apart, 0.112 in.Dia hole for plug

# Material:

Steel comp 8740 or steel comp 4140

# **Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response

# Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

# **Thread Series Designator:**

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

# NSN 5305-01-075-7092

Panel Fastener Screw - Page 2 of 2

# Mil-std (military Standard):

Mil-s-6049 spec.

