NSN 5305-01-075-8534

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-075-8534

| view Online at https://aerobasegroup.com/hsil/5303-01-075 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.452 inches and 0.482 inches |
| Fastener Length: |
| Between 1.014 inches and 1.044 inches |
| Head Style: |
| Oval countersunk |
| Head Diameter: |
| Between 0.469 inches and 0.474 inches |
| Grip Diameter: |
| Between 0.3115 inches and 0.3120 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| 0.562 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel |
| Material Specification: |
| 23-112, tyd, fscm 76301 mfr ref single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |

