## NSN 5305-01-076-4900

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-076-4900

Thread Class:
3a

Thread Direction:
Right-hand
Thread Length:
Between 0.408 inches and 0.500 inches

Fastener Length:

Between 0.470 inches and 0.500 inches

Head Style:

Flat chamfer

**Head Diameter:** 

Between 0.218 inches and 0.226 inches

**Head Height:** 

Between 0.134 inches and 0.138 inches

**Locking Feature:** 

Patch threads

**Internal Drive Style:** 

Hexagon

**Thread Diameter:** 

0.138 inches

Width Across Flats:

Between 0.1094 inches and 0.1111 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

**Hardness Rating:** 

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

155000 pounds per square inch

Material:

Steel

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Thread Series Designator:** 

Unc

**Specification Data:** 

82918-bacs12bw manufacturers standard

Shelf Life:

N/a

## NSN 5305-01-076-4900

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0