## NSN 5305-01-076-4930

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-076-4930

view Online at https://aerobasegroup.com/nsn/5305-01-076-493
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.443 inches and 0.510 inches
Fastener Length:
Between 1.015 inches and 1.062 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.456 inches and 0.508 inches
Head Height:
Between 0.065 inches and 0.067 inches
Shoulder Diameter:
0.2646 inches first shoulder and 0.2651 inches first shoulder
Shoulder Length:
0.485 inches first shoulder and 0.507 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Special Features:
Furnished with one rubber o ring
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5305-01-076-4930

Shoulder Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0