NSN 5305-01-076-4932

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-076-4932 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.505 inches and 0.572 inches **Fastener Length:** Between 1.077 inches and 1.124 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.575 inches and 0.635 inches **Head Height:** Between 0.082 inches and 0.084 inches **Shoulder Diameter:** 0.3271 inches first shoulder and 0.3276 inches first shoulder **Shoulder Length:** 0.468 inches first shoulder and 0.490 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one rubber o ring Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-01-076-4932

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0