## NSN 5305-01-076-4945

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-076-4945 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.250 inches and 0.300 inches **Fastener Length:** Between 0.448 inches and 0.478 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.2702 inches and 0.3016 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp 8740 **Material Specification:** Mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 1 cl 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-076-4945

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.