

View Online at <https://aerobasegroup.com/nsn/5305-01-076-6316>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.390 inches and 0.437 inches

Fastener Length:

Between 0.890 inches and 0.937 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.3765 inches and 0.3813 inches

Head Height:

Between 0.0439 inches and 0.0459 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Grip Length:

0.500 inches

Features Provided:

O ring

Thready Qty Per Inch (tpi):

32

Countersink Angle:

100.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Stainless steel fastener

Material Specification:

Mil-r-25988 type 1, cl 1, grade 70 military specification single material response primary washer

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-r-25988 spec.