

View Online at <https://aerobasegroup.com/nsn/5305-01-076-8100>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.426 inches and 0.475 inches

**Fastener Length:**

Between 0.470 inches and 0.500 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.105 inches and 0.119 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.060 inches

**Thready Qty Per Inch (tpi):**

80

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp 321 or steel comp 347 or steel comp 303 or steel comp 303se or steel comp 302

**Screw Material Specification:**

Qq-s-763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or astm a582 assn standard 3rd material response or astm a582 assn standard 4th material response or mil-s-7720 military specification 5th material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas662 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-7720 spec.