## NSN 5305-01-077-1004

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-077-1004

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.316 inches and 0.366 inches
Fastener Length:
Between 0.820 inches and 0.850 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.355 inches and 0.397 inches
Shoulder Diameter:
0.2646 inches first shoulder and 0.2651 inches first shoulder
Shoulder Length:
0.382 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Countersink Angle:
Countersink Angle: Between 99.0 degrees and 101.0 degrees
Between 99.0 degrees and 101.0 degrees
Between 99.0 degrees and 101.0 degrees  Shoulder Shape:
Between 99.0 degrees and 101.0 degrees  Shoulder Shape:  Round first shoulder
Between 99.0 degrees and 101.0 degrees  Shoulder Shape:  Round first shoulder  Special Features:
Between 99.0 degrees and 101.0 degrees  Shoulder Shape: Round first shoulder  Special Features: Socket drive recess in thd end width across flats 0.1270 in. Min 0.1296 in. Max
Between 99.0 degrees and 101.0 degrees  Shoulder Shape: Round first shoulder  Special Features: Socket drive recess in thd end width across flats 0.1270 in. Min 0.1296 in. Max  Material:
Between 99.0 degrees and 101.0 degrees  Shoulder Shape:  Round first shoulder  Special Features:  Socket drive recess in thd end width across flats 0.1270 in. Min 0.1296 in. Max  Material:  Steel comp xm-13
Between 99.0 degrees and 101.0 degrees  Shoulder Shape: Round first shoulder  Special Features: Socket drive recess in thd end width across flats 0.1270 in. Min 0.1296 in. Max  Material: Steel comp xm-13  Material Specification:
Between 99.0 degrees and 101.0 degrees  Shoulder Shape: Round first shoulder  Special Features: Socket drive recess in thd end width across flats 0.1270 in. Min 0.1296 in. Max  Material: Steel comp xm-13  Material Specification: Ams 5629 assn standard single material response
Between 99.0 degrees and 101.0 degrees  Shoulder Shape: Round first shoulder  Special Features: Socket drive recess in the end width across flats 0.1270 in. Min 0.1296 in. Max  Material: Steel comp xm-13  Material Specification: Ams 5629 assn standard single material response  Surface Treatment:
Between 99.0 degrees and 101.0 degrees  Shoulder Shape: Round first shoulder  Special Features: Socket drive recess in thd end width across flats 0.1270 in. Min 0.1296 in. Max  Material: Steel comp xm-13  Material Specification: Ams 5629 assn standard single material response  Surface Treatment: Passivate
Between 99.0 degrees and 101.0 degrees  Shoulder Shape: Round first shoulder  Special Features: Socket drive recess in thd end width across flats 0.1270 in. Min 0.1296 in. Max  Material: Steel comp xm-13  Material Specification: Ams 5629 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification:
Between 99.0 degrees and 101.0 degrees  Shoulder Shape: Round first shoulder  Special Features: Socket drive recess in thd end width across flats 0.1270 in. Min 0.1296 in. Max  Material: Steel comp xm-13  Material Specification: Ams 5629 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Between 99.0 degrees and 101.0 degrees  Shoulder Shape: Round first shoulder  Special Features: Socket drive recess in thd end width across flats 0.1270 in. Min 0.1296 in. Max  Material: Steel comp xm-13  Material Specification: Ams 5629 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator:
Between 99.0 degrees and 101.0 degrees  Shoulder Shape: Round first shoulder  Special Features: Socket drive recess in thd end width across flats 0.1270 in. Min 0.1296 in. Max  Material: Steel comp xm-13  Material Specification: Ams 5629 assn standard single material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator: Unjf

--

## NSN 5305-01-077-1004

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0