NSN 5305-01-077-4833

Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-077-4833

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.688 inches and 0.875 inches
Fastener Length:
Between 0.844 inches and 0.875 inches
Head Style:
Hexagon
Head Height:
Between 0.226 inches and 0.243 inches
Width Between Flats:
Between 0.5510 inches and 0.5625 inches
Hole Diameter:
Between 0.0605 inches and 0.0685 inches
Thread Diameter:
0.375 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
120000 pounds per square inch
Hardness Rating:
25.0 rockwell c and 34.0 rockwell c
Hole Configuration Style:
Hexagon flats
Criticality Code Justification:
Zzzy
Surface Finish:
63.0 microinches threads
Material:
Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020
or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp
1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel
comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541
Material Specification:
66 federal standard all material responses
Surface Treatment:

Special quality control testing

Cadmium and chromate

Special Test Features:

NSN 5305-01-077-4833

Hexagon Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-416 type 2 cl2 federal specification single treatment response

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread	Series	Design	ator:

Unc

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A003b0