## NSN 5305-01-077-7905

Thumbscrew - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-077-7905 Thread Class: 2a Thread Direction: Right-hand Thread Length: 0.120 inches Fastener Length: 0.400 inches Head Style: Knurled no. 4 Head Diameter: 0.250 inches Head Height: 0.400 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diamete 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thread Y Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment: Passivate
2a Thread Direction: Right-hand Thread Length: 0.120 inches Fastener Length: 0.400 inches Head Style: Knurled no. 4 Head Diameter: 0.250 inches Head Height: 0.400 inches First Diameter From Head: 0.75 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Thread Direction: Right-hand Thread Length: 0.120 inches Fastener Length: 0.400 inches Head Style: Knurled no. 4 Head Diameter: 0.250 inches Head Height: 0.400 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Right-hand Thread Length: 0.120 inches Fastener Length: 0.400 inches Head Style: Knurled no. 4 Head Diameter: 0.250 inches Head Height: 0.250 inches Head Height: 0.250 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diameted 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Thread Length: 0.120 inches Fastener Length: 0.400 inches Head Style: Knurled no. 4 Head Diameter: 0.250 inches Head Height: 0.400 inches First Diameter From Head: 0.400 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Stainless steel
0.120 inches Fastener Length: 0.400 inches Head Style: Knurled no. 4 Head Diameter: 0.250 inches Head Height: 0.250 inches Head Height: 0.400 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Stainless steel Surface Treatment:
Fastener Length:         0.400 inches         Head Style:         Knurled no. 4         Head Diameter:         0.250 inches         Head Height:         0.400 inches         First Diameter From Head:         0.075 inches         Distance From Largest Bearing Surface Of Head To End Of First Diameter         0.280 inches         Point Style:         Flat         Thread Diameter:         0.112 inches         Thready Qty Per Inch (tpi):         40         Externally Relieved Body Diameter Quantity:         1         Material:         Stainless steel         Surface Treatment:
0.400 inches Head Style: Knurled no. 4 Head Diameter: 0.250 inches Head Height: 0.400 inches First Diameter From Head: 0.400 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Stainless steel Surface Treatment:
Head Style: Knurled no. 4 Head Diameter: 0.250 inches Head Height: 0.400 inches First Diameter From Head: 0.400 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Knurled no. 4 Head Diameter: 0.250 inches Head Height: 0.400 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Head Diameter: 0.250 inches Head Height: 0.400 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
0.250 inches Head Height: 0.400 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Head Height: 0.400 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
0.400 inches First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
First Diameter From Head: 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Distance From Largest Bearing Surface Of Head To End Of First Diame 0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
0.280 inches Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Point Style: Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Flat Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
40 Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
Externally Relieved Body Diameter Quantity: 1 Material: Stainless steel Surface Treatment:
1 Material: Stainless steel Surface Treatment:
Material: Stainless steel Surface Treatment:
Stainless steel Surface Treatment:
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
No
Fiig: A003b0