Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-077-9066

| Thread Olympic |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.140 inches and 0.172 inches |
| Fastener Length: |
| Between 0.280 inches and 0.312 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.205 inches and 0.219 inches |
| Head Height: |
| Between 0.070 inches and 0.080 inches |
| First Diameter From Head: |
| Between 0.080 inches and 0.083 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.140 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.112 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Stainless steel |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |