

View Online at <https://aerobasegroup.com/nsn/5305-01-078-2929>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.380 inches and 0.447 inches

**Fastener Length:**

Between 1.078 inches and 1.125 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.377 inches and 0.381 inches

**Head Height:**

Between 0.044 inches and 0.046 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.678 inches and 0.698 inches

**Thread Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Stainless steel

**Material Specification:**

23-112, fscm 76301 mfr ref single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Specification Data:**

76301-st3-652 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0