NSN 5305-01-078-4446

Demilitarization:

No

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-078-4446 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.111 inches and 0.121 inches **Fastener Length:** 0.385 inches **Head Style:** Flat countersunk **Head Diameter:** 0.225 inches **First Diameter From Head:** Between 0.067 inches and 0.077 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.215 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 98.0 degrees and 102.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Stainless steel **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment:** Passivate and oxide **Surface Treatment Specification:** Qq-p-35, type 2 federal specification 1st treatment response or mil-c-13924, cl4 military specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

NSN 5305-01-078-4446

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.