NSN 5305-01-078-4457

Setscrew - Page 1 of 1





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.115 inches and 0.135 inches

Fastener Length:

Between 0.115 inches and 0.135 inches

Head Style:

Headless (setscrew)

Locking Feature:

Patch threads or pellet threads or strip threads

Point Style:

Cone

Internal Drive Style:

.....

Hexagon

Thread Diameter:

0.112 inches

Width Across Flats:

0.050 inches

Thready Qty Per Inch (tpi):

40

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

1 type and 2 style

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig: