NSN 5305-01-078-4463

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-078-4463



Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.650 inches and 0.700 inches **Fastener Length:** Between 0.910 inches and 0.940 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.795 inches and 0.813 inches **Head Height:** Between 0.230 inches and 0.245 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.438 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1578 professional/industrial association standard

N/a

Shelf Life:

NSN 5305-01-078-4463

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0