NSN 5305-01-078-5064

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-078-5064 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.501 inches **Fastener Length:** 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.099 inches and 0.110 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 120000 pounds per square inch Hardness Rating: 23.0 rockwell c fastener and 40.0 rockwell c fastener **Primary Washer Outside Diameter:** Between 0.365 inches and 0.381 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.018 inches and 0.024 inches **Material Specification:** Aisi assn standard all material responses primary washer **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-01-078-5064

Assembled Washer Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0