## NSN 5305-01-078-5070

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-078-5070 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.449 inches and 0.489 inches **Fastener Length:** Between 0.636 inches and 0.676 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.4640 inches and 0.5066 inches **Head Height:** Between 0.070 inches and 0.073 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.1562 inches and 0.1585 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** 100.0 degrees Surface Finish: 32.0 microinches threads **Special Features:** Furnished with one o ring Material: Iron alloy 660 **Material Specification:** Ams5732 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Qq-p-35, type 1, type 2, type 3 or type 6 federal specification single treatment response

**Thread Series Designator:** 

Unjc

## NSN 5305-01-078-5070

Socket Head Cap Screw - Page 2 of 2



| _ |   |   |     | - |      |  |
|---|---|---|-----|---|------|--|
| C | h | Δ | Iŧ. |   | ife: |  |
|   |   |   |     |   |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0