

View Online at <https://aerobasegroup.com/nsn/5305-01-078-5072>

**Fastener Length:**

Between 0.950 inches and 1.000 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

Between 0.307 inches and 0.358 inches

**Width Between Flats:**

Between 0.551 inches and 0.562 inches

**Extended Washer Diameter:**

Between 0.720 inches and 0.780 inches

**Extended Washer Thickness:**

Between 0.037 inches and 0.063 inches

**Internal Drive Style:**

W/o internal drive

**Features Provided:**

Casehardened

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 38.0 rockwell c

**Nonmachine Thread Style:**

Blunt (type tt)

**Nonmachine Thread Diameter:**

0.375 inches

**Material:**

Steel comp 4037

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl2 federal specification single treatment response or mil-c-81562 type 2 cl 2 military specification single treatment response

**Specification Or Standard:**

B type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-81562 spec.