NSN 5305-01-078-5072

Tapping Screw - Page 1 of 2

A003b0



View Online at https://aerobasegroup.com/nsn/5305-01-078-5072

view Offilite at https://aerobasegroup.com/nish/0505-01-070-3072
Fastener Length:
Between 0.950 inches and 1.000 inches
Head Style:
Hexagon extended washer
Head Height:
Between 0.307 inches and 0.358 inches
Width Between Flats:
Between 0.551 inches and 0.562 inches
Extended Washer Diameter:
Between 0.720 inches and 0.780 inches
Extended Washer Thickness:
Between 0.037 inches and 0.063 inches
nternal Drive Style:
N/o internal drive
Features Provided:
Casehardened
Min. Tensile Strength (psi):
150000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 38.0 rockwell c
Nonmachine Thread Style:
Blunt (type tt)
Nonmachine Thread Diameter:
0.375 inches
Material:
Steel comp 4037
Material Specification:
66 federal standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl2 federal specification single treatment response or mil-c-81562 type 2 cl 2 military specification single treatment
response
Specification Or Standard:
3 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg:

NSN 5305-01-078-5072

Tapping Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-81562 spec.